

APC Back-UPS™ 650

Part Number: BX650LI



Battery Backup Protection for Computers and Electronics

The Back-UPS 650 from APC by Schneider Electric protects your computer and electronic equipment from destructive power outages by providing short term battery power during an outage. The Back-UPS 650 features Automatic Voltage Regulation (AVR), which instantly adjusts high and low voltage fluctuations to safe levels for your electronics, saving battery power for when you need it most during storms and power outages. Equipped with IEC sockets, the BX650LI keeps your desktop computer, monitor or other critical devices (router, modem, television, etc.) running when the power goes out. Specifically designed to protect electronic equipment in harsh power environments, the Back-UPS 650 ensures maximum productivity and work efficiency.



Product Features

1 LED Indicator and Audible Alarms

Quickly understand the unit and power status through visual and audible indicators.

2 Automatic Voltage Regulation (AVR)

“Boost and Trim” AVR instantly corrects voltage fluctuations without using the battery, allowing you to work indefinitely through inconsistent power, saving battery life for power outages.

3 4 IEC Battery Backup Sockets

Keep critical electronic equipment running when the power goes out, so you can protect your work and save your data.

4 Automatic Diagnostic Testing

Periodic battery self-test ensures early detection of a battery that needs to be replaced, ensuring your unit is ready when you need it.

5 2 Yr Warranty

APC offers a 2 year warranty with free technical phone and online support, providing customer peace of mind.

6 Easy to use “one step” battery connector.



APC
by Schneider Electric

Back-UPS BX650LI Specifications

| | |
|---|--|
| Model Number | BX650LI |
| Output | |
| Output Capacity | 650 VA / 325 Watts |
| Output Voltage / Frequency (On utility) | 230V / 45-65 Hz |
| Output Voltage / Frequency (On battery) | 230V, 50 or 60 Hz +/-1 Hz (auto-sensing) |
| Output Connections | 4 IEC 320 C13 sockets (all with battery backup protection) |
| Waveform Type | Stepped Approximation to Sine Wave |
| Input | |
| Input Voltage / Frequency | 180 – 270 V, 50/60Hz +/-1Hz (default:50Hz) |
| Input Connection | IEC-320 C14 |
| Physical | |
| Unit Dimensions (H x W x D) | 142 x 101 x 300 mm |
| Unit Weight | 4.2 Kg |
| Shipping Dimensions (H x W x D) | 223 x 143 x 347 mm |
| Shipping Weight | 4.58 Kg |
| Color | Black |
| UPC Code | 731304318194 |
| Battery | |
| Battery Type | Maintenance-free, sealed lead-acid battery, leak proof |
| Battery Size | 12 volt, 7 Ah |
| Management | |
| Alarms | Visual (LED) and audible alarms |
| Adjustable Sensitivity and Transfer Voltage | Low, Medium (default), High |
| Conformance | |
| Warranty | 2 years repair or replace (excluding battery) and 1 year for battery |
| Regulatory Approvals | CE, EAC |

APC by Schneider Electric

132 Fairgrounds Rd
West Kingston, RI 02892

www.apc.com

